

# iNetVu 9000 Controller



## Online with the touch of a button . . .

- ◆ Simple one touch operation to Find Satellite and Stow Antenna
- ◆ Quickly acquires signal in 3 to 5 minutes
- ◆ Optimal Antenna Pointing Calculations
- ◆ Automatically stows iNetVu Mobile Platform
- ◆ Integrated with a growing list of Satellite Modems and VSATs

## Modem Compatibility

### HNS Direcway

DW4000  
DW4020  
DW6000  
DW7000  
DW7700

### ViaSat

LinkStar II  
LinkStar IV

### EMS

SIT Series 2000  
SIT Series 3000

### Gilat/StarBand

Gilat 360 / 360E  
StarBand 360  
StarBand 481  
StarBand 484  
SkyEdge

### Comtech

CDM-570L  
CDM-600L

### Nera

SatLink 1000  
SatLink 1910

### iDirect

NetModem II  
NetModem II Plus  
iNFINITI 3000  
iNFINITI 5000  
iNFINITI 7000

### TechniSat

SkyStar 2 TV PCI Receiver  
SkyStar USB Receiver

### Tachyon

CI-1300

## iNetVu 9000 Controller Features

- ◆ One Box Solution: Easy to install, configure, and operate
- ◆ Eliminates need for PC
- ◆ No software installation required
- ◆ 19" 1U Rack Mountable Unit
- ◆ LCD Display and Keypad Navigator
- ◆ Automatic and Manual Control Keypad
- ◆ Compatible with all iNetVu Mobile Platforms
- ◆ Remote Access/Monitor via Web Interface
- ◆ Plugs directly to 110-240 VAC

## Physical

Dimensions: L: 17.5"; W: 13.0"; H: 1.75"  
Weight: 15 lbs.

## I/O

GPS Module: SMA Connector  
RF Rx: Type F Connector  
Signal Input: DB26 Connector  
Motor Control: 9-Pin Circular AMP Connector  
Web Interface: RJ45 Female

Optional External Keyboard, Monitor, Mouse Ports available.

## Electrical

Power Input 100 - 240 VAC, 3 - 6 A, 50 - 60 Hz

Elevation: 12 VDC, 12 A Max.

Azimuth: 12 VDC, 8 A Max.

Polarization: 12 VDC, 2 A Max

Fuse: 15 A Fast Blow

## Misc.

Operating Temperature: 0 - 50°C (32 - 122°F)

